

523 Shown in Satin Aluminum



522



523

#### UPDATED 6/17

# **522-16 LED** Optional **522-20 LED** Optional 523 LED ADA Optional

### **LUMINOUS BOWL W/TRIM RING**





print this page



<u>≡</u> email this page to a colleague



installation instructions



interactive submittal drawing

#### **COMPANIONS**





#### **FEATURES**

- Transitional design fits contemporary or traditional spaces.
- Companion ceiling & pendant fixtures.
- 522 available in two sizes.
- 523 is ADA compliant.

#### **ECO INFO**

METALS: Sand cast mounting back is made from 100% recycled aluminum. Other aluminum and brass parts have the highest available recycled content for lower embodied energy and are valuable and recyclable at the end of the product's useful life. For more information see "GENERAL INFO"

FINISHING: Solid, natural metal finishes are sealed with a hand-applied bees wax. No paint or lacquer is used in order to avoid pollution associated with the manufacture and application of these substances. Clear coat finishes are available. Paint finishes are low VOC and oven cured.

**ENERGY:** Designed exclusively for compact fluorescent lamps using HPF electronic ballasts or LEDs.

#### **MATERIALS**

- · Solid aluminum or brass metal work, hand finished.
- Luminous bowl is white acrylic with a matte finish.

#### **FINISHES**

**SAL** Satin Aluminum

MW Matte White

SB Satin Brass

**CCP** Custom Color Painted finish

**AB** Antique Brass

Standard metal finishes are hand satined and waxed.

#### **LAMPING**

**CF:** 522-16 or 522-20: 2-CF13DTT or 2-CF26TTT.

523: 2-CF13DDT

LED: 522-16: 1-GU24 base A19, 12W, 1100 lumens

522-20: 2-LED A-lamps as above.

523: 1-10W array, 1600 lumens, 3000k, 80+CRI.

LED A-lamps triac dimmable, 3000K, supplied.

#### **BALLAST/DRIVER**

CF: Integral electronic HPF, 120V/277V.

LED A-lamp: Electronic driver is built into the lamp, 120V only. 523 LED: Integral driver is 120/277V and 0-10V dimmable.





522-16 shown in Satin Aluminum.

#### **OPTIONS**

FAUX: Hand applied faux finish available. Specify FAUX.

**DIMMING: CF:** Lutron & Advance dimming available.


LED A-lamps: Triac dimmable, 120V only.


523 LED: 0-10V dimmable/ Triac dimming available.

**EMERGENCY BATTERY PACK:** Remote mounted EBP,

specify **REM**. Not available for **LED**.

## 522-16 522-20 **523**





MOUNTING: Standard J-box or plaster ring.

WEIGHT: 4 lbs

### **VARIATIONS / MODIFICATIONS**

Special finishes

☐ FAUX

□ REM

• Addition of decorative detail

#### SPEC GUIDE SAMPLE SPEC: 523-CF2/13-120-SB-FAUX

#### LAMPING -- FINISH - OPTION CAT# -SIZE V0LT **5**22 **1**6 ☐ CF2/13 **1**20 □ SAL **2**0 ☐ CF2/26\* ☐ AB **□** 523 **277** Note: 523 only \*Not available □ SB available. 16" for 523. ■ MW ☐ LED1/12 ☐ CCP ☐ LED2/12

☐ LED/10



