

UPDATED 8/15

# **533** *NEW* ADAILED

## **DIRECT SCONCE**





print this page



 $\equiv \boxed{}$  email this page to a colleague



installation instructions



interactive submittal drawing

Shown in Satin Aluminum



#### **FEATURES**

- Purpose-built for LED
- ADA compliant.
- Unique shape fits many architectural styles.

# **ECO INFO**

**METALS:** Aluminum parts have the highest available recycled content for lower embodied energy. All metals are valuable and recyclable at the end of the product's useful life.

For more information see "GENERAL INFO"

FINISHING: Solid, natural metal finishes are sealed with a hand-applied bees wax. No paint or lacquer is used in order to avoid pollution associated with the manufacture and application of these substances. Clear coat finishes are available. Paint finishes are low VOC and oven cured.

**ENERGY:** Designed exclusively for LEDs using HPF electronic drivers.

#### **MATERIALS**

· Aluminum, hand finished.

### **FINISHES**

**SAL** Satin Aluminum

MW Matte White

**CCP** Custom Color Painted finish

Standard metal finishes are hand satined and waxed. Other metal finishes are available. Contact factory.

#### **LAMPING**

1-9W LED array, 1210 lumens each or 1-14W, 1650 lumens each, both 3000K, 80 CRI. LED arrays are replaceable with quick connects.


## **DRIVER**


Integral HPF electronic driver is 120 volt and is triac dimmable. 0-10V dimming available for 120 & 277V.











# **VARIATIONS / MODIFICATIONS**

- Special finishes
- Addition of decorative detail

**NOTE:** Standard electronic driver is multi-volt and 0-10V dimmable. Two-wire incandescent dimming is available for 120V.

**MOUNTING:** Standard J-box or plaster ring.

WEIGHT: 4 lbs

SPEC GUIDE SAMPLE SPEC: 553-LED1/10-277-SAL

CAT# - LAMPING -- FINISH VOLT **5**33 □ LED1/9 **1**20 □ SAL ☐ LED1/14 **2**77 ☐ MW  $\Box$  CCP



